

1AER AEROSOLS Page 1 of 1

- FEATURES

 - Remarkably Versatile
 - Ideal for repairs and touch ups
- USES

Interior and exterior - Dependant on Paint product

CLEANER FOR EQUIPMENT

APPLICATION EQUIPMENT Aerosol Spray Can with adjustable fan

APPLICATION

- Shake vigorously for at least one minute after rattling of mixing ball is heard. Shake intermittently during application.
- For best results spray at temperatures between 10c - 30c
- Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
- Mask areas not to be sprayed to protect from overspray.
- Hold can 12 to 16 inches from surface. Press spray button firmly. Do not apply with continuous spray. Use back and forth motion, keeping can in a level line with surface.
- For best results 3-4 thin coats are recommended rather than one heavy coat.
- Do not insert pins or other sharp objects into valve opening.

FURTHER INFORMATION **IMPORTANT:** When spraying is complete, turn can upside down and press nozzle for 3-5 seconds. This will completely clean the nozzle head and avoid any blocking during future use.



Coverage	Touch Dry	Recoat Time	Max Resistance	Pot Life	Mix Ratio	Shelf Life	Pack Size
1 Sq.m/400mil	10-15 mins	60 mins	N/A	N/A	N/A	12 months	400mil

158/16

