

LEAR **Leather Renovator - Repair System** **Page 1 of 1**

FEATURES	<ul style="list-style-type: none"> • Formulation is based upon top quality ingredients • Uniforms minor cracks & repairs • Excellent opacity, easily re-coatable • Gives a high degree of water resistance when fully dry. 	
USES	Repairer for scuffs & scratches on leather soles.	
TOPCOAT	DRN-3-CL010-005	11880/10 Leather Top Coat Clear MATT
	DRN-3-CL035-005	11880/35 Leather Top Coat Clear SATIN
	DRN-3-CL090-005	11880/90 Leather Top Coat Clear GLOSS
BASECOAT	DRN-6-AA000-005	11840 Leather Renovator Promatch
	DRN-6-AS000-005	11840 Leather Renovator Promatch SPECIAL
	DRN-6-BL000-005	11840 Leather Renovator Black
	DRN-6-WH000-005	11840 Leather Renovator White
CLEANER FOR SUBSTRATE	DRN-9-11830-005	11830 Intense Leather WB Cleaner
CLEANER FOR EQUIPMENT	ZI330	WATER
APPLICATION EQUIPMENT	By sponge or lint free cloth or spray	
APPLICATION	Clean surface with 11830 Intense cleaner, When surface is dry, apply 11840 leather renovator by sponge or spray. Apply directly onto & around the fault. Lightly blend. When dry (approx 30mins) a second coat may be applied to ensure an even finish. Once second coat is fully dry (Min 4 hours) apply a full even coat 11880 clear top coat (available in various sheen levels) to finally seal the coating & gives added wear & UV protection.	
FURTHER INFORMATION	Protect product from freezing.	



Coverage	Touch Dry	Recoat Time	Max Resistance	Pot Life	Mix Ratio	Shelf Life	Pack Size
9-11 Sq.m/lit	15-20 mins	30 mins	7 days	N/A	N/A	12 months	1, 5 & 20lt

152/16

