

ST1

INTERLAC (Polystyrene) Finish

Page 1 of 1

FEATURES

- Quick drying with good flow properties
- Excellent Gloss & Colour retention
- Suitable for fast production schedules
- Hardwearing, marr resistant. Contains anti-scuff additives

USES

Coating for flexible & rigid Polystyrene

TOPCOAT

ST1-3-CL010-005	INTERLAC Styrene Clear 10% Sheen
ST1-3-CL025-005	INTERLAC Styrene Clear 25% Sheen
ST1-3-CL050-005	INTERLAC Styrene Clear 50% Sheen
ST1-3-CL090-005	INTERLAC Styrene Clear 90% Sheen
ST1-6-AA000-005	INTERLAC Styrene Promatch
ST1-6-AA00E-005	INTERLAC Styrene Promatch Metallic
ST1-6-AS000-005	INTERLAC Promatch SPECIAL

BASECOAT

ST1-7-WH010-005	INTERLAC 18347 Styrene Primer White
ST1-7-CH010-005	INTERLAC Styrene Primer Charcoal
ST1-7-GR010-005	INTERLAC Styrene Primer Grey

THINNER FOR SYSTEM

SRT-9-TH574-005	No 574 Styrene Thinners
-----------------	-------------------------

CLEANER FOR SUBSTRATE

CL2-9-TH040-005	No 40 Solvent Degreaser
-----------------	-------------------------

CLEANER FOR EQUIPMENT

CL2-9-TH020-005	ISF Spray Gun & Brush Cleaner
-----------------	-------------------------------

APPLICATION EQUIPMENT

Conventional airless / airmix or HVLP spray equipment.

APPLICATION

Clean substrate with 40 Degreaser. May be used as a single coat application - Use INTERLAC Primer to fill slight surface imperfections. Apply a full wet coat by conventional spray equipment.

FURTHER INFORMATION

Thinners not normally required - add up to maximum 10% if needed.

Please note: This product can also be supplied in 400 ml Aerosols with professional adjustable fan nozzels.



Coverage	Touch Dry	Recoat Time	Max Resistance	Pot Life	Mix Ratio	Shelf Life	Pack Size
----------	-----------	-------------	----------------	----------	-----------	------------	-----------

8-10 Sq.m/lit	5 mins	60 mins	7 Days	N/A	N/A	12 months	1, 5 & 25lt
---------------	--------	---------	--------	-----	-----	-----------	-------------

