

## CR1

## Chlorinated Rubber Finish

Page 1 of 1

### FEATURES

- High build, highly resistant & water resistant system
- Easy application single pack product with good coverage
- Resistant to swimming pool vapour. Easily re-coatable
- Used to coat galvanised heat ducts

### USES

Interior & exterior metal, Even concrete.

### TOPCOAT

CR1-6-AA000-005	Chlorinated Rubber Finish Promatch
CR1-6-AS000-005	Chlorinated Rubber Finish Promatch SPECIAL
CR1-6-BL090-005	Chlorinated Rubber Finish Black
CR1-6-WH090-005	Chlorinated Rubber Finish White

### CLEANER FOR SUBSTRATE

CL2-9-TH040-005 No 40 Solvent Degreaser

### CLEANER FOR EQUIPMENT

CL2-9-TH020-005 ISF Spray Gun & Brush Cleaner

### APPLICATION EQUIPMENT

Brush, conventional spray or HVLP spray equipment.

### APPLICATION

Ensure substrate is clean using No 40 degreaser. Add CRP thinners up to 10% volume. Once cured, the coating will resist water, mild acids & alkalines.

### FURTHER INFORMATION

Please note: CRP should not be used in conjunction with other paint systems - either underneath or over coating.



Coverage	Touch Dry	Recoat Time	Max Resistance	Pot Life	Mix Ratio	Shelf Life	Pack Size
8-10 Sq.m/ltr	20-30 mins	4 hrs	7 Days	N/A	N/A	12 months	1, 5 & 25lt

