

QD3

RAPIDO SPATTER (Super-Fast Enamel)

Page 1 of 1

FEATURES

- Developed to meet today's busy production deadlines
- Exceptionally fast dry times
- Excellent opacity & sanding
- Hardwearing, marr resistant. Contains anti-scuff additives

USES

Interior FERROUS metals & Joinery

TOPCOAT

QD3-6-AA000-005 RAPIDO (Super-Fast Enamel) Promatch
QD3-6-AA0ME-005 RAPIDO (Super-Fast) Promatch METALLIC
QD3-6-AS000-005 RAPIDO (Super-Fast) Promatch SPECIAL

BASECOAT

QD3-7-GR000-005 RAPIDO Primer GREY
QD3-7-WH000-005 RAPIDO Primer WHITE

CLEANER FOR EQUIPMENT

CL2-9-TH020-005 ISF Spray Gun & Brush Cleaner

APPLICATION EQUIPMENT

Conventional airless / airmix or HVLP spray equipment.

APPLICATION

Degrease substrate with No 40 Degreaser. Ensure primer is sanded well prior to top coat being applied. Apply by normal spray techniques. READY FOR USE - Thinners not usually required as this will affect the SPATTER finish holding up. Only use onto FERROUS metals.

FURTHER INFORMATION

IMPORTANT: Please ensure that primer is sanded well between coats.
Please note: This product can also be supplied in 400 ml Aerosols with professional adjustable fan nozzles.



Coverage
406

Touch Dry

Recoat
Time

Max
Resistance

Pot Life

Mix Ratio

Shelf Life

Pack Size

6-9 Sq.m/lt

2-5 mins

60 mins

7 Days

N/A

N/A

12 months

1, 5 & 25lt

152/16

