

Hi Opacity 2k Floor Paint (Concrete)

Page 1 of 1

FEATURES

- Based upon a top quality epoxy resin formulation
- Outstanding adhesion & superb filling properties
- Resistant to chemical spillages & easily re-coatable
- Internal & External grade

USES

High quality 2k coating for Concrete Flooring

TOPCOAT

Hi Opacity 2k Floor Paint (Concrete) Promatch
Hi Opacity 2k Floor Paint (Concrete) Frigate Grey
Hi Opacity 2k Floor Paint (Concrete) Slate Grey
Hi Opacity 2k Floor Paint (Concrete) Tile Red

TOPCOAT CATALYST

TP2-8-NO.01-001 TP2 Catalyst (1lt)

THINNER FOR SYSTEM

TPT-9-TH150-005 No 150 Two Pack Thinners

CLEANER FOR SUBSTRATE

CL2-9-TH040-005 No 40 Solvent Degreaser

CLEANER FOR EQUIPMENT

CL2-9-TH020-005 ISF Spray Gun & Brush Cleaner

APPLICATION EQUIPMENT

By brush, roller, mop or conventional spray equipment

APPLICATION

Generally applied as a 'one coat' finish with a recoat time after 12 hours in normal conditions if required. It is advised when applying to new or uncoated concrete to thin the first coat 1:1 with No 150 Thinners, this will allow the product to flow into the pores of the concrete and act as a sealer, once this is done leave overnight to dry, then apply a second coat of neat product to achieve a hard wearing durable floor coating.
Before applying please ensure that the floor is thoroughly clean, dry & sound.

FURTHER INFORMATION

Gives excellent adhesion onto plastics & metal substrates (ferrous, aluminium, stainless steel).



Coverage	Touch Dry	Recoat Time	Max Resistance	Pot Life	Mix Ratio	Shelf Life	Pack Size
9-11 Sq.m/lit	60 mins	12 Hrs	7 Days	12 Hours	4 : 1	12 months	5 & 25lt

