



*the perfect finish*  
SINCE 1898

MANUFACTURING INNOVATIVE  
SOLUTIONS FOR OVER 125 YEARS

## ISF TECHNICAL DATA SHEET

# Aerosol Spray Can - 400ml



### FEATURES

- Remarkably Versatile
- Ideal for repairs and touch ups
- Varied Solvent based systems available

### USES

Interior and exterior - Dependant on Paint product

### PRODUCT

Check product availability with ISF Sales team

### APPLICATION PROCESS

- Shake vigorously for at least one minute after rattling of mixing ball is heard, intermittently during application
- For best results spray at temperatures between 10°C - 20°C
- Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants
- Mask areas not to be sprayed to protect from overspray
- Hold can 12 to 16 inches from surface. Press spray button firmly. Do not apply with continuous spray
- Use back and forth motion, keeping can in a level line with surface
- For best results 3-4 thin coats are recommended rather than one heavy coat
- Do not insert pins or other sharp objects into valve opening

### FURTHER INFORMATION

IMPORTANT: When spraying is complete, turn can upside down and press nozzle for 3-5 seconds. This will completely clean the nozzle head and avoid any blocking during future use



AEROSOL Pre-charged 400ml | Page 1 of 1

*This version: March 2025*

