



*the perfect finish*  
SINCE 1898

MANUFACTURING INNOVATIVE  
SOLUTIONS FOR OVER 125 YEARS

## ISF TECHNICAL DATA SHEET

# POLYFIX Adhesion Promoter



### FEATURES

- Used extensively in the plastics & adhesives industry
- Easy application

USES	Advanced adhesion promoter for Polypropylene substrates
TOPCOAT	PVC (Spray) Promatch TP5 (Acrylic Epoxy) Promatch
CLEANER FOR SUBSTRATE	No 40 Solvent Degreaser
CLEANER FOR EQUIPMENT	ISF Spray Gun & Brush Cleaner
APPLICATION EQUIPMENT	Dip, brush or conventional airless / airmix or HVLP spray equipment.

### APPLICATION PROCESS

Stir & mix the product well prior to use, supplied as 'ready for use' viscosity for hand or spray application.

- Clean substrate with No 40 Solvent Degreaser
- Apply by Dip, Brush or Spray and allow to dry
- Touch dry 15mins
- Only when fully dry (approx. 2hrs) may it then be overcoated with the recommended ISF topcoat
- Coverage: 15-20sqm

### FURTHER INFORMATION

This product can also be supplied in 400 ml Aerosols with professional adjustable fan nozzles.  
Storage Temperatures should be maintained above 5°C.



POLYFIX Adhesion Promoter | Page 1 of 1

*This version: March 2025*

