



*the perfect finish*  
SINCE 1898

MANUFACTURING INNOVATIVE  
SOLUTIONS FOR OVER 125 YEARS

## ISF TECHNICAL DATA SHEET

# THIXOFILLA Grain Filler



### FEATURES

- Thixotropic grain filler based on oil-based resins
- Easily re-coatable with all topcoats
- Interior use

<b>USES</b>	To fill the grain before polishing or lacquering to achieve a "full finish"
<b>TOPCOAT</b>	THIXOFILLA Jeco J025 Neutral THIXOFILLA Jeco J025 Promatch
<b>CLEANER FOR EQUIPMENT</b>	ISF Spray Gun & Brush Cleaner
<b>APPLICATION EQUIPMENT</b>	Hessian cloth.

### APPLICATION PROCESS

Stir & mix the product well prior to use.

Apply with coarse cloth i.e. Curtaining or Hessian in a circular motion, finishing off across the grain. Leave until the 'wet look' has gone then wipe off across the grain with a clean coarse cloth to remove the excess. Leave to dry overnight then sand with 150-180 grit. THIXOFILLA will except most stains and can be finished with most types of lacquers and polishes. Coverage 8-10sqm/lt.

### FURTHER INFORMATION

Storage Temperatures should be maintained above 5°C.



THIXOFILLA Grain Filler | Page 1 of 1

*This version: March 2025*

