

STG5 Steri-Guard Leather Renovator **Page 1 of 1**

FEATURES	<ul style="list-style-type: none"> • Formulation is based upon top quality ingredients • Uniforms minor cracks & repairs • Excellent opacity, easily re-coatable • Gives a high degree of water resistance when fully dry.
USES	Repairer for scuffs & scratches on leather.
TOPCOAT	SGL-6-AA000-005 Steri-Guard Leather Renovator Promatch
CLEANER FOR SUBSTRATE	DRN-9-11830-005 11830 Intense Leather WB Cleaner
CLEANER FOR EQUIPMENT	Z1330 WATER
APPLICATION EQUIPMENT	By sponge or lint free cloth or spray
APPLICATION	Clean surface with 11830 Intense cleaner, When surface is dry, apply Steri-Guard leather renovator by sponge or spray. Apply directly onto & around the fault. Lightly blend. When dry (approx 30mins) a second coat may be applied to ensure an even finish. Once second coat is fully dry (Min 4 hours) apply a full even coat Steri-Gaurd clear top coat (available in various sheen levels) to finally seal the coating & gives added wear & UV protection.
FURTHER INFORMATION	Protect product from freezing.



Coverage	Touch Dry	Recoat Time	Max Resistance	Pot Life	Mix Ratio	Shelf Life	Pack Size
9-11 Sq.m/ltr	15-20 mins	30 mins	7 days	N/A	N/A	12 months	5lt

